

Hardeners

Table

Symbol	Name	Packaging		Use of	Mixing ratio	Use at ambient temperature [°C]
		Unit	Collective (box)			
CP 255	Hardener MS	500 ml	6 pcs	CP 250 MS	2:1	15-25
CP 288	Hardener MS	500 ml	6 pcs	CP 400 MS	2:1	15-25
		2,5 L	4 pcs			
CP 3014	Hardener UHS	250 ml	10 pcs	CP 2014 UHS	4:1	15-25
		1 L	6 pcs			
CP 3015	Hardener HS	500 ml	6 pcs	CP 2015 HS	2:1	15-25
CP 216	Hardener HS	150 ml	(in the set with primer)	CP 388 HS, CP 345 HS	depends on kind of primer	15-25
		250 ml				
		500 ml	6 pcs			
		1 L	6 pcs			
CP 285	Hardener MS	500 ml	6 pcs	CP 400 MS, CP 1500 MS, CM 10, CP 88 Premium	2:1	15-25
		2,5 L	4 pcs			
		5 L	4 pcs			
CP 286	Hardener MS slow	500 ml	6 pcs	CP 400 MS, CP 1500 MS, CM 10, CP 88 Premium	2:1	25-35
		2,5 L	4 pcs			
		5 L	4 pcs			
CP 282	Hardener MS fast	500 ml	6 pcs	CP 400 MS, CP 1500 MS, CM 10, CP 88 Premium	2:1	10-20
		2,5 L	4 pcs			
		5 L	4 pcs			
CP 245	Hardener	500 ml	(in the set with CP 590)	CP 590	2:1	15-25
CP 295	Hardener HS	150 ml (150 g)	(in the set with CP 395)	CP 395	4:1	15-25
CP 208	Hardener HS	500 ml	6 pcs	CP 2008 HS	2:1	15-25
CP 297	Hardener MS	500 ml	6 pcs	CP 400 MS, CP 88 Premium, CP 365, CP 362	depends on kind of product	15-25
		1 L	6 pcs			
		5 L	4 pcs			
CP 218	Hardener MS „air dry“	1 L	6 pcs	CP 400 MS, CP 1500 MS, CP 88 Premium	2:1	10-20
		5 L	5 pcs			

The recipe of the product complies with the VOC guidelines. The products supplied by our company are subject to a number of factory tests, so they can meet the highest demands. However, be aware of the individual conditions of storage, preparation and applications that can influence on the effect of varnishing. The guarantee to keep the highest quality of the coating is to use the product only with the products of the Manufacturer and in accordance with the recommendations of the Manufacturer. The Manufacturer does not guarantee performance and compatibility of the Products with products other than those of the Manufacturer. In order to recognise the guarantee and all claims, the user shall use the technologies and techniques for using the Products - according to the technical data sheet and execute the sample spray prior to target painting.