

EASY

Universal polishing compound



EASY consists of highly efficient sanding particles ensuring maximum intensity of surface polishing.

It removes marks of polishing (with P2500) in only one work flow process to create a well-preserved coating surface with high gloss.

It contains no silicone and can be used on all popular coating system.

Packaging	
Unit	Collective (box)
1 L	6 pcs
125 ml	12 pcs
20 ml	200 pcs

Type of coating

Fresh OEM Coatings
Fresh Repair Coatings
Aged/weather-worn Coatings

Sanding Papers with grid*

P2500-P3000

Polishing pads

Lambswool;
Foam pads:
White (hard);
Yellow (medium);
Orange (soft).

During machine polishing the best results will be achieved with rotating 1500–2000 RpM.

Date of minimum durability:

24 months (in the original unopened package)

The recipe of the product complies with the VOC guidelines. The products supplied by our company are subject to a number of factory tests, so they can meet the highest demands. However, be aware of the individual conditions of storage, preparation and applications that can influence on the effect of varnishing. The guarantee to keep the highest quality of the coating is to use the product only with the products of the Manufacturer and in accordance with the recommendations of the Manufacturer. The Manufacturer does not guarantee performance and compatibility of the Products with products other than those of the Manufacturer. In order to recognize the guarantee and all claims, the user shall use the technologies and techniques for given Products - according to the technical data sheet and execute the sample spray prior to target painting.